

Ser. No. 09/941,884

RECEIVED
CENTRAL FAX CENTER

2

60003206-1

OCT 02 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

entering a diagnostic mode of the printing system in which mode normal printing jobs of the printing system are not printed;

while in said diagnostic mode, printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes, to accumulate media advance error between the printing of the different areas, said printing different areas of a diagnostic pattern performed without any intervening printing of a normal print job; and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

2. (Previously Presented) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

entering a diagnostic mode of the printing system in which mode normal printing jobs of the printing system are not printed;

printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes, to accumulate media advance error between the printing of the different areas; and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action; and

wherein said printing different areas comprises:

Ser. No. 09/941,884

3

60003206-1

printing a first area comprising a first set of pixels printed during a first pass;

conducting a plurality of incremental media advances;

printing a further area comprising a second set of pixels printed during a further pass, wherein media advance errors resulting from said plurality of media advances are accumulated between printing said first area and printing said further area.

3. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

during a diagnostic mode of the printing system in which normal printing jobs of the printing system are not printed, printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes without any intervening printing of a normal print job, to accumulate media advance error between the printing of the different areas, wherein said different areas are nominally aligned along a horizontal line; and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

4. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes without any intervening printing of a normal print job, to accumulate media advance error between the printing of the different areas; and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action, wherein said step of examining the diagnostic pattern is conducted visually by a user.

Ser. No. 09/941,884

4

60003206-1

5. (Original) The method of Claim 1, wherein said step of examining the diagnostic pattern is conducted by an optical sensor comprising the printing system.

6. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

checking for printhead health and taking any corrective needed action to recover nozzle health;

during a diagnostic mode in which normal printing jobs of the printing system are not printed, printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes without any intervening printing of a normal print job, to accumulate media advance error between the printing of the different areas; and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

7. (Original) The method of Claim 1, wherein said step of printing different areas of a diagnostic plot includes:

applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels, with each pixel location having a number associated therewith, the number representing the pass in which the pixel will be printed, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed.

8. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

Ser. No. 09/941,884

5

60003206-1

during a diagnostic mode of the printing system in which normal printing jobs of the printing system are not printed, printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes without any intervening printing of a normal print job, to accumulate media advance error between the printing of the different areas, said printing different areas of a diagnostic pattern comprising applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels and a row width of w pixels, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed, and wherein said diagnostic print mode mask defines that the first $w/2$ pixels in the row are printed in the same pass (a_i), and the last $w/2$ pixels in the row are printed in another pass (b_i); and

examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

9. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

during a diagnostic mode of the printing system in which normal printing jobs of the printing system are not printed, printing different areas of a diagnostic pattern at different passes of one or more ink-jet printheads with a controlled amount of media advances between the passes without any intervening printing of a normal print job, to accumulate media advance error between the printing of the different areas, said printing of a diagnostic pattern comprising applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than

Ser. No. 09/941,884

6

60003206-1

said second set of pixels is printed, said diagnostic print mode mask defines that the first w/2 pixels in the row are printed in the same pass (a_i), and the last w/2 pixels in the row are printed in another pass (b_i), wherein said diagnostic print mode mask includes a row wherein said first w/2 pixels are printed in a first pass, and said last w/2 pixels are printed in a last pass of said plurality of passes; and examining the diagnostic pattern to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

10. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode in which mode normal printing jobs of the printing system are not printed;

printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas without any intervening printing of a normal print job; and

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

11. (Previously Presented) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode in which mode normal printing jobs of the printing system are not printed;

Ser. No. 09/941,884

7

60003206-1

printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas; and

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action; and

wherein said printing different areas comprises:

printing a first area comprising a first set of pixels printed during a first pass;

conducting a plurality of incremental media advances;

printing a further area comprising a second set of pixels printed during a further pass, wherein media advance errors resulting from said plurality of media advances are accumulated between printing said first area and printing said further area.

12. (Original) The method of Claim 10 wherein said different areas are nominally aligned along a horizontal line.

13. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode;

printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas without any intervening printing of a normal print job; and

BEST AVAILABLE COPY

BEST AVAILABLE COPY

Ser. No. 09/941,884

8

60003206-1

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action, wherein said step of examining the diagnostic pattern is conducted visually by a user.

14. (Original) The method of Claim 10, wherein said step of examining the diagnostic pattern is conducted by an optical sensor comprising the printing system.

15. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode;

checking for printhead health and taking any corrective needed action prior to printing a diagnostic pattern;

printing different areas of the diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas without any intervening printing of a normal print job; and

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

16. (Original) The method of Claim 10, wherein said step of printing different areas of a diagnostic plot includes:

applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels, with each pixel location having a number associated therewith, the number representing the pass in which the pixel will be printed, and wherein said different

Ser. No. 09/941,884

9

60003206-1

areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed.

17. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode;

printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas and without any intervening printing of a normal print job, said printing different areas of a diagnostic plot comprising applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels and a row width of w pixels, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed, wherein said diagnostic print mode mask defines that the first $w/2$ pixels in the row are printed in the same pass (a_i), and the last $w/2$ pixels in the row are printed in another pass (b_i); and

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

18. (Currently Amended) A diagnostic method for visual detection of poor media advance calibration in an ink-jet printing system, comprising:

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

Ser. No. 09/941,884

10

60003206-1

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode;

printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas without any intervening printing of a normal print job, said printing different areas of a diagnostic plot comprising applying a diagnostic multi-pass print mode mask, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels and a row width of w pixels, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed, said diagnostic print mode mask defining that the first $w/2$ pixels in the row are printed in the same pass (a_i), and the last $w/2$ pixels in the row are printed in another pass (b_i), wherein said diagnostic print mode mask includes a row wherein said first $w/2$ pixels are printed in a first pass, and said last $w/2$ pixels are printed in a last pass of said plurality of passes; and examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.

19. (Canceled)

20. (Currently Amended) A multi-pass diagnostic print mode mask for printing a diagnostic plot to enhance visual detection of poor media advance calibration in an ink-jet printing system including a printhead having a nozzle array, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels and a row width of w pixels, with each pixel location having a number associated therewith, the number representing the pass in which the pixel will be printed, and wherein said different areas include a first

Ser. No. 09/941,884

11

60003206-1

set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed, wherein said diagnostic print mode mask defining that the first $w/2$ pixels in the row are printed in the same pass (a_i), and the last $w/2$ pixels in the row are printed in another pass (b_i), and wherein the diagnostic plot is printed without any intervening printing of a normal print job.

21. (Currently Amended) A multi-pass diagnostic print mode mask for printing a diagnostic plot to enhance visual detection of poor media advance calibration in an ink-jet printing system including a printhead having a nozzle array, wherein a plurality of carriage passes are employed to print the area subtended by a printhead nozzle array, the diagnostic print mode mask comprising a rectilinear grid of pixels and a row width of w pixels, and wherein said different areas include a first set of pixels on a row of said grid, and a second set of pixels on said row, and wherein said first set of pixels is printed on a different pass than said second set of pixels is printed, said diagnostic print mode mask defining that the first $w/2$ pixels in the row are printed in the same pass (a_i), and the last $w/2$ pixels in the row are printed in another pass (b_i), and wherein said diagnostic print mode mask includes a row wherein said first $w/2$ pixels are assigned to be printed in a first pass, and said last $w/2$ pixels are assigned to be printed in a last pass of said plurality of passes, and wherein the diagnostic plot is printed without any intervening printing of a normal print job.

22. (Currently Amended) A diagnostic method for improving print quality in an ink-jet printing system, comprising;

providing an ink-jet printhead mounted on a carriage, the carriage mounted for movement along a scan axis;

providing a media advance system for advancing a print medium along a media path which is transverse to the scan axis;

entering a diagnostic multi-pass print mode;

determining whether the nozzle array has good health;

Ser. No. 09/941,884

12

60003206-1

if the nozzle array has good health, printing different areas of a diagnostic plot at different passes using said ink-jet printhead with a controlled amount of media advances between the passes to accumulate media advance error between the printing of the different areas: without any intervening printing of a normal print job; and

examining the diagnostic plot to determine whether the accumulated media advance error is sufficiently objectionable to take corrective action.